

Decobase B



DECOLOR

»Hiša barv«

Wood Coatings

Basic, preventive impregnation for wood based on inorganic and organic biocides.



DESCRIPTION

DECObase B is a coating/impregnation for wood intended for basic/preventive wood protection against biological pests, wood insects, blue stain fungi and wood-decay fungi.

It is used as a first layer or base protection for new wood intended for making roofs, fences, terraces, log houses, facade linings, builders' joinery (windows, doors, shutters etc.).

The impregnation soaks into the wood very well; active substances affix in 24 hours. Wood exposed to weather or atmospheric influences should be additionally protected with a glaze coating from the Decolazur product range; this procedure is also used to decoratively paint wood the desired hue, to improve its resistance against effects of weather and UV rays and to simultaneously create a barrier so that biocides cannot come into contact with the environment.

CONTAINERS AND STORAGE

Containers:

Plastic jerrycans: 1 kg, 5 kg, 10 kg, 20 kg

Plastic barrel: 60 kg, 200 kg, IBC tank 1,000 kg

Storage:

In a dry and closed room, at temperatures between +5°C and +35°C, protected against frost and direct exposure to the sun and in the original/closed container.

APPLICATION

Tools: Brush, roller, paint tray, garden hose.

Cleaning: Tools should be cleaned with water and detergent immediately after use.

Warning: During application, the floors of the working area should be covered with an impermeable covering that will prevent the product spilling into the environment. Ensure the safe use of biocides. Before use, always read the label and data on the product.

CHARACTERISTICS

- Basic, preventive protection for new wood (mainly structural woodwork) against biological pests, wood insects, blue stains and decay
- Effective active substances
- Active substances affix in 24 hours
- Does not create a layer and binds with the wood
- Suitable for all types of wood
- Certificate from the Ljubljana Biotechnical Faculty

USE

Instructions for Work: Decobase B is ready for use as supplied. It can be applied to healthy, clean and dry wood (max 20% humidity content). The optimum temperature for work is between +5°C to +35°C, relative humidity must not exceed 85%. During work, use suitable protective clothing (suitable goggles, gloves, overalls, footwear). Do not apply the product onto wood that is intended to be in contact with animals or feedstuffs (beehive, manger, sauna etc.).

Hues: Yellow, light or dark brown and green (other hues available by order).

Coverage: 1 kg of impregnation is suitable for preserving approx. 5m² of surface. The coverage depends on the type and quality of the wood (humidity), its surface treatment and method of application. Larger coverage means higher wood protection.

Drying: Approximately 3 hours. Drying time depends on the temperature of the atmosphere when product is being applied and wood humidity. Coating with a Decolazur finish/glaze coat is recommended after min. 24 hours.



DECOLOR

Decolor d.o.o. ■ Osredke 8 ■ 1262 Dol pri Ljubljani ■ Slovenija ■ info@decolor.si ■ www.decolor.si