

# Decowall

## Exterior & Interior



**DECOLOR**  
» House of colors «

### Wall paints

Super-washable, matt, water-based wall paint for interior and exterior use.



#### DESCRIPTION

**DECOWALL Exterior & Interior** is vinyl-siloxane, super-washable, matt, water-based paint with high covering power and excellent expansion; suitable for both interior and exterior application. It is ideal for plaster, plasterboard, putty walls and shaved mineral surfaces in general. It allows excellent recovery on intermediate coat works, perfectly masking plaster imperfections and it avoids streaking effect. Its formula is studied through the most recent and avantgarde technologies of modern chemical industry.

#### PACKAGING & STORAGE

##### Packaging units:

Metal packaging: 1l, 2,7l, 9l.

##### Storage:

In original and closed can at temperature from +5°C to +25°C, protected from the direct sunlight and frost, out of reach of children.

#### APPLICATION

**Tools:** Long-bristle fur or textile paint roller (length of hairs or threads is 18 to 20 mm); also the following can be used: natural and artificial fur or textile linings made of different synthetic threads – polyamid, dralon, vestan, nylon, perlon, or polyester), or a painting brush suitable for application of dispersion wall paints or by spraying. Use a bucket grid when applying the paint with a roller.

##### Cleaning:

Immediately after use thoroughly clean the tools with water.

#### CHARACTERISTICS

- Highly resistant to wet scrubbing
- Excellent coverage
- Extremely low content of vaporous organic substances
- Easy to apply
- Available in a wide range of colourshades
- High water vapour permeability
- For both indoor and outdoor use

#### USE

**Instructions for work:** Decowall Exterior & Interior Premium is, in delivered form, ready for use.

Surface should be solid, dry and clean with no badly adhered particles, dust, oil stains or other filth. From already painted surfaces, remove all paint coats and precoats containing oil paints, lacquers and enamels which get easily and quickly off with cloth soaked in water with usual household cleaners. Surfaces infected with wall mould must be disinfected prior to painting. Stir the paint well before use and dilute it with water up to 50 % for first layer and 40 % for second layer (both with water). Paint is applied in two coats, 4 to 6 hours apart (T = +20°C, relative air humidity = 65 %). An individual wall surface is painted without interruptions from one end to the other. Always treat first the surfaces inaccessible to a standard long-bristle paint roller or to spraying gun (corners, gutters, narrow reveal surfaces, and similar) first using suitable brushes or smaller paint rollers adjusted to existing conditions. Painting is possible only in suitable weather or microclimate conditions: temperature of the air and the wall surface should not be lower than +5°C and not higher than +35°C and relative air humidity should not be higher than 80 %.

**Shades:** Base A (white), Base C (transparent).

**Consumption:** 120-170 ml/m<sup>2</sup> for a two-coat application (consumption depends of the surface conditions).

